

Active infrared beams



Accessories

 SB11/16/21/26/31 Kit for 2-sided view	 SB53 Socket for SB series pillar	 SB18 AIR Pillar climbing detector	 PB50-H 12V non polarity heater 250mA for beam tower
 PB50-T Thermostat for beam tower	 PB50-AC180 PB50-AC360 Anti climb top tamper for 180°/360° beam towers	 SB52 Power Supply 230VAC to 12VAC & 12VDC	 BS121N Sealed Lead-Acid Battery 12V 1.2Ah VdS approved

Applications





SB series

Beams

- SB250-N** AIR stand alone twin beam, 50m range
- SB2100-N** AIR stand alone twin beam, 100m range
- SB450-N** AIR stand alone quad beam, 50m range
- SB4100-N** AIR stand alone quad beam, 100m range
- SB4200-N** AIR stand alone quad beam, 200m range

Pillars

- SB10** Empty pillar 1 m
- SB15** Empty pillar 1.5 m
- SB20** Empty pillar 2 m
- SB25** Empty pillar 2.5 m
- SB30** Empty pillar 3 m

PB series

Beams

- PB501** Twin AIR beam 20m outdoor/40m indoor
- PB511** Twin AIR beam 40m outdoor/80m indoor
- PB521** Twin AIR beam 60m outdoor/120m indoor
- PB601** Outdoor Quad AIR beam 50m
- PB611** Outdoor Quad AIR beam 100m
- PB621** Outdoor Quad AIR beam 200m

Pillars

- PB10** 1m – 180° AIR Beam Tower
- PB15** 1.5m – 180° AIR Beam Tower
- PB20** 2m – 180° AIR Beam Tower
- PB30** 3m – 180° AIR Beam Tower
- PB11** 1m – 360° AIR Beam Tower
- PB16** 1.5m – 360° AIR Beam Tower
- PB21** 2m – 360° AIR Beam Tower
- PB31** 3m – 360° AIR Beam Tower

Outdoor motion sensors



Accessory



DI601-WT
Walk tester for DI601 and DDI602 series

Applications





DI601, DDI602 series

- DI601** Outdoor PIR 10/20/30m - 33/66/98ft selectable
- DI601-WT** Walk tester for DI601 and DDI602 series
- DDI602-F1** Outdoor Dual Technology detector 10.525 GHz 10/20/30m - 33/66/98ft selectable
- DDI602-F2** Outdoor Dual Technology detector 10.587 GHz 10/20/30m - 33/66/98ft selectable
- DDI602-F3** Outdoor Dual Technology detector 9.9 GHz 10/20/30m - 33/66/98ft selectable

TX-2810 series

- TX-2810-03-4** Wireless Outdoor PIR 868AM Gen2

Outdoor microwave sensors



Accessories

 MRW01 Alignment tool	 MRW02-N Power supply 230 VAC/19 VAC with IP66 enclosure
 MRW03 Pair of inox poles 120cm	 BS122N Sealed Lead-Acid Battery 12V 2.2Ah

Applications





MRW Series

The Netherlands, Belgium, UK, Denmark, Italy, Sweden, Ireland, Poland, Norway, Finland

- MRW50-F1** Outdoor Microwave Motion Sensors, 10.5 GHz, 50m
- MRW100-F1** Outdoor Microwave Motion Sensors, 10.5 GHz, 100m
- MRW200-F1** Outdoor Microwave Motion Sensors, 10.5 GHz, 200m

France, Austria, Portugal, Czech Republic

- MRW50-F2** Outdoor Microwave Motion Sensors, 9.9 GHz, 50m
- MRW100-F2** Outdoor Microwave Motion Sensors, 9.9 GHz, 100m
- MRW200-F2** Outdoor Microwave Motion Sensors, 9.9 GHz, 200m

Spain, Luxembourg

- MRW50-F4** Outdoor Microwave Motion Sensors, 10.525 GHz, 50m
- MRW100-F4** Outdoor Microwave Motion Sensors, 10.525 GHz, 100m
- MRW200-F4** Outdoor Microwave Motion Sensors, 10.525 GHz, 200m

Fence, roof and wall protection sensors



Accessories

 DF950-CM Universal Configuration Module (UCM) Software kit with interface cable	 DF863 Splice and Terminator Kit for microphonic cable	 DF852 Non-sensitive lead-in cable for microphonic sensor cable, 30m roll
 DF962 Quick disconnect gate assembly kit	 DF963 Gate Bypass Module, Locally Activated by Keyswitch	 DF964 Gate Bypass Module, remotely activated by computer control

Applications





Fence protection

- DF951** FlexPS processor in NEMA 4 enclosure, 12-48 VDC

Network option

- DF955-C1** Multi-mode fiber (MMF) comm card
- DF955-C2** EIA-422 copper comm card
- DF955-U** Fence protection Network Interface Unit
- DF955-SW** Network Manager SW CD
- KTP-12DCU-UK** Switching Power Supply, 1A, 12VDC
- DF851** Fence protection microphonic sensor cable - 300m (984 ft) roll

Roof / Wall protection

- DF450** FlexPI processor in rugged plastic enclosure